

XTS 902 DUAL VOLTAGE WATER COOLER



Technical Information

| Parameter | Value |
|--------------------------|--------------|
| Input Voltage | 110V/230V 1P |
| Weight empty | 19.5kg |
| Tank capacity | 5L |
| Motor rating 230V | 3.0A |
| Motor rating 110V | 6.6A |
| Heat Exchanger Rating | 900W |
| Max. Water Temperature | +60°C |
| Max. Ambient Temperature | +40°C |
| Noise | 74dba |

| Stock Code | Description |
|-------------|--|
| XTS902 | Dual Voltage Water Cooler |
| XTS902FS | Dual Voltage Water Cooler with Flow Switch |
| XTS902-P1 | Dual Voltage Water Cooler c/w 10L Ultracool |
| XTS902FS-P1 | Dual Voltage Water Cooler c/w Flow Switch, 10L Ultracool |

Options

| Stock Code | Description |
|------------|-------------------------------|
| XTSUC | Parweld Ultracool Coolant 10L |
| XTSFSK | Flow Switch Kit |
| XTSH1 | Hook Up Kit x 1m |
| XTSH3 | Hook Up Kit x 3m |

- Dual Voltage 110V/230V
- Suitable for use with MIG and TIG Plant up to 500A
- Available with Flow Switch to Protect the Torch
- Quick Connectors for Rapid Hook Up
- Small Foot Print allows location on the Cylinder Stand of Machines
- No Pump Priming Required
- 24 Months Return to Base Warranty
- Manufactured to IP21S, ISO/IEC 60974-1, ISO/IEC 60974-6 and RoHS Compliant

XTS 905 WATER COOLER



Technical Information

| Parameter | Value |
|--------------------------|-----------|
| Input Voltage | 400V / 3P |
| Weight empty | 19.5kg |
| Tank capacity | 5L |
| Motor rating 230V/400V | 1.5A |
| Heat Exchanger Rating | 900W |
| Max. Water Temperature | +60°C |
| Max. Ambient Temperature | +40°C |
| Noise | 74dba |

| Stock Code | Description |
|-------------|--|
| XTS905 | Dual Voltage Water Cooler |
| XTS905FS | Dual Voltage Water Cooler with Flow Switch |
| XTS905-P1 | Dual Voltage Water Cooler c/w 10L Ultracool |
| XTS905FS-P1 | Dual Voltage Water Cooler c/w Flow Switch, 10L Ultracool |

Options

| Stock Code | Description |
|------------|-------------------------------|
| XTSUC | Parweld Ultracool Coolant 10L |
| XTSFSK | Flow Switch Kit |
| XTSH1 | Hook Up Kit x 1m |
| XTSH3 | Hook Up Kit x 3m |
| XTSH1-303 | Hook Up Kit x 1m XTI 303 |
| XTSH3-303 | Hook Up Kit x 3m XTI 303 |

To order 230V Version use Stock Code XTS904

- Voltage 400V
- Suitable for use with MIG and TIG Plant up to 500A
- Available with Flow Switch to Protect the Torch
- Quick Connectors for Rapid Hook Up
- Small Foot Print allows location on the Cylinder Stand of Machines
- No Pump Priming Required
- 24 Months Return to Base Warranty
- Manufactured to IP21S, ISO/IEC 60974-1, ISO/IEC 60974-6 and RoHS Compliant