

NEW XTS 162 MMA INVERTER

With Lift TIG Function (Single Voltage)



- 230V Input
- Lightweight 8.5kg
- 160A @ 20% Duty Cycle
- Easy Electrode Striking with Arc Force
- Easy Electrode Re-striking with Hot Start
- Connections 35-50mm Dinse
- Supplied with Electrode Holder, 3m Cable, 3m Earth Lead and Wire Brush
- Over Voltage and Over Current Protection
- Digital Amperage Display
- Welding Mode for Rutile and Low Hydrogen Electrodes
- Manufactured to IP21S, ISO/IEC 60974-1, ISO/IEC 60974-6 and RoHS Compliant

Stock Code

XTS162	160A MMA Inverter 230V
XTS162-P1	MMA Inverter with WP17V Torch Package

Description

Technical Information

Parameter	Value
Output Current	20-160A
Input Voltage	230V 1P
Input Current (Max)	30A
Maximum Electrode Size	3.2mm
No Load Voltage	78V
Cable Connection	35-50 Dix
Duty Cycle	160A@ 20%
Fuse Rating	16A
KVA	5.4
Enclosure Protection	IP23S
Dimensions (mm)	350 x 160 x 246
Weight (kg)	8.5

Accessory Information

Stock Code	Description
CKE203	Electrode Holder Cable Kit x 3m
CKC203	Earth Cables Clamp Kit x 3m
WP17-V-12-2IX	WP17 Scratch Start TIG Torch x 12.5ft
E700123	Argon Regulator Single Stage 2 Gauge
WP17AK	TIG Spares Kit in Plastic Case
XR935H	Everyday Light Reactive Welding Helmet
XTICC	Carry Case (Sold separately)

Multi Mode

The XTS 162 MMA has dedicated welding modes for rutile and cellulosic electrodes. The touch button interface is easy to use and ideal for harsh environments.

Electrodes up to 3.2mm can be used with ease.

TIG Welding

By fitting the optional TIG torch and coupling to a suitable gas supply the XTS 162 can be used for TIG welding and is suitable for welding steel and stainless steel.

The lift arc mode limits the arc current when the tungsten touches the work piece preventing electrode damage.

Generator Friendly

The XTS 162 is able to cope with inputs which fluctuate by +/- 15% and can be used with the majority of generators.

The machine is housed in a rugged steel case. A carry case is available as an optional extra.